



## HANDHELD DATA COLLECTION MADE EASY

The TITAN products are the most versatile inventory data collection terminals available.

## PERFORMANCE & RELIABILITY

- Durable case withstands harsh environments and considerable abuse
- Full-travel keyboard will accurately process data as fast as you can press the keys
- Extremely low power consumption ensures the industry's longest battery life
- USB communication for system upgrade and data export
- State-of-the-art technology
- 12 Month new product warranty

## **POWER & FLEXIBILITY**

With 5 embedded programs the TITAN 2500 Handheld allows you to get your inventory up and running quickly and yet it is powerful enough to handle the most demanding inventory.

## EXPERIENCE & DEDICATION

A.S.T., Inc. has more than 33 years of experience developing and manufacturing data collection software and hardware. You can find our products throughout North America, South America, Europe, and Asia.



Whatever your needs, A.S.T., Inc. will exceed your expectations!



TITAN 2500





	Hardware Specifications
CPU:	ARM-based 32-bit 200 MHz CPU
Firmware/Operating System:	Proprietary firmware for standard operation included in TITAN
	TITAN 2500 Handheld includes 5 embedded program options:
	Area, Section, \$, Qty
Applications:	Area, \$, Qty
	Area, Section, Dept, \$, Qty
	Area, Dept, \$, Qty
	Area, Dept, \$, Qty w/Decimal
Memory:	4 MB EEPROM - Operating system and code storage
	1 MB SRAM - Data storage
	2 MB Flash memory - Backup data storage
Communicatione	30 MB Flash memory
Communications: Data Transfer:	USB for system updates and data export
	USB (TITAN to PC) - 12 Mbps
Data Fault Protection:	Data is fully protected, even from hardware faults & electrostatic discharge
Power Management:	Proprietary power management for maximum battery life
	Super-capacitor provides 100 hours of data retention without batteries
Audio:	Piezo buzzer for error and extended price limit notification.
Physical Specifications	
Discontinue	11.63" L x 5.25" W x 3.88" H
Dimensions:	11.63" L x 5.25" W x 3.88" H Display: 2.9" W x .95" H
	11.63" L x 5.25" W x 3.88" H Display: 2.9" W x .95" H Keyboard: 5.5" L x 4.5" W
Display:	11.63" L x 5.25" W x 3.88" H Display: 2.9" W x .95" H Keyboard: 5.5" L x 4.5" W 4 Line x 20 Character Supertwist (STN) LCD
Display: Key switches:	11.63" L x 5.25" W x 3.88" H Display: 2.9" W x .95" H Keyboard: 5.5" L x 4.5" W 4 Line x 20 Character Supertwist (STN) LCD Full travel, Light touch
Display: Key switches: Keypad:	11.63" L x 5.25" W x 3.88" H Display: 2.9" W x .95" H Keyboard: 5.5" L x 4.5" W 4 Line x 20 Character Supertwist (STN) LCD Full travel, Light touch 29 key alphanumeric
Display: Key switches:	11.63" L x 5.25" W x 3.88" H Display: 2.9" W x .95" H Keyboard: 5.5" L x 4.5" W 4 Line x 20 Character Supertwist (STN) LCD Full travel, Light touch 29 key alphanumeric 32 oz (907 grams)
Display: Key switches: Keypad: Weight (including battery):	11.63" L x 5.25" W x 3.88" H Display: 2.9" W x .95" H Keyboard: 5.5" L x 4.5" W 4 Line x 20 Character Supertwist (STN) LCD Full travel, Light touch 29 key alphanumeric 32 oz (907 grams) Six AA batteries - 200 hours of usage*
Display: Key switches: Keypad: Weight (including battery): Battery life:	11.63" L x 5.25" W x 3.88" H Display: 2.9" W x .95" H Keyboard: 5.5" L x 4.5" W 4 Line x 20 Character Supertwist (STN) LCD Full travel, Light touch 29 key alphanumeric 32 oz (907 grams) Six AA batteries - 200 hours of usage* *Based on 250kspm average data accumulation
Display: Key switches: Keypad: Weight (including battery): Battery life: Operating Temperature:	11.63" L x 5.25" W x 3.88" H Display: 2.9" W x .95" H Keyboard: 5.5" L x 4.5" W 4 Line x 20 Character Supertwist (STN) LCD Full travel, Light touch 29 key alphanumeric 32 oz (907 grams) Six AA batteries - 200 hours of usage* *Based on 250kspm average data accumulation -4°F to 158°F, -20°C to 70°C
Display: Key switches: Keypad: Weight (including battery): Battery life: Operating Temperature: Storage Temperature:	11.63" L x 5.25" W x 3.88" H Display: 2.9" W x .95" H Keyboard: 5.5" L x 4.5" W 4 Line x 20 Character Supertwist (STN) LCD Full travel, Light touch 29 key alphanumeric 32 oz (907 grams) Six AA batteries - 200 hours of usage* *Based on 250kspm average data accumulation -4°F to 158°F, -20°C to 70°C -22°F to 176°F, -30°C to 80°C
Display: Key switches: Keypad: Weight (including battery): Battery life: Operating Temperature: Storage Temperature: Humidity:	11.63" L x 5.25" W x 3.88" H Display: 2.9" W x .95" H Keyboard: 5.5" L x 4.5" W 4 Line x 20 Character Supertwist (STN) LCD Full travel, Light touch 29 key alphanumeric 32 oz (907 grams) Six AA batteries - 200 hours of usage* *Based on 250kspm average data accumulation -4°F to 158°F, -20°C to 70°C -22°F to 176°F, -30°C to 80°C 0% to 90% (Operating and Storage)
Display: Key switches: Keypad: Weight (including battery): Battery life: Operating Temperature: Storage Temperature: Humidity: Drop Spec:	11.63" L x 5.25" W x 3.88" H Display: 2.9" W x .95" H Keyboard: 5.5" L x 4.5" W 4 Line x 20 Character Supertwist (STN) LCD Full travel, Light touch 29 key alphanumeric 32 oz (907 grams) Six AA batteries - 200 hours of usage* *Based on 250kspm average data accumulation -4°F to 158°F, -20°C to 70°C -22°F to 176°F, -30°C to 80°C 0% to 90% (Operating and Storage) Multiple five foot drops to concrete
Display: Key switches: Keypad: Weight (including battery): Battery life: Operating Temperature: Storage Temperature: Humidity:	11.63" L x 5.25" W x 3.88" H Display: 2.9" W x .95" H Keyboard: 5.5" L x 4.5" W 4 Line x 20 Character Supertwist (STN) LCD Full travel, Light touch 29 key alphanumeric 32 oz (907 grams) Six AA batteries - 200 hours of usage* *Based on 250kspm average data accumulation -4°F to 158°F, -20°C to 70°C -22°F to 176°F, -30°C to 80°C 0% to 90% (Operating and Storage) Multiple five foot drops to concrete 8KV Human model
Display: Key switches: Keypad: Weight (including battery): Battery life: Operating Temperature: Storage Temperature: Humidity: Drop Spec:	11.63" L x 5.25" W x 3.88" H Display: 2.9" W x .95" H Keyboard: 5.5" L x 4.5" W 4 Line x 20 Character Supertwist (STN) LCD Full travel, Light touch 29 key alphanumeric 32 oz (907 grams) Six AA batteries - 200 hours of usage* *Based on 250kspm average data accumulation -4°F to 158°F, -20°C to 70°C -22°F to 176°F, -30°C to 80°C 0% to 90% (Operating and Storage) Multiple five foot drops to concrete
Display: Key switches: Keypad: Weight (including battery): Battery life: Operating Temperature: Storage Temperature: Humidity: Drop Spec:	11.63" L x 5.25" W x 3.88" H Display: 2.9" W x .95" H Keyboard: 5.5" L x 4.5" W 4 Line x 20 Character Supertwist (STN) LCD Full travel, Light touch 29 key alphanumeric 32 oz (907 grams) Six AA batteries - 200 hours of usage* *Based on 250kspm average data accumulation -4°F to 158°F, -20°C to 70°C -22°F to 176°F, -30°C to 80°C 0% to 90% (Operating and Storage) Multiple five foot drops to concrete 8KV Human model
Display: Key switches: Keypad: Weight (including battery): Battery life: Operating Temperature: Storage Temperature: Humidity: Drop Spec: ESD:	11.63" L x 5.25" W x 3.88" H Display: 2.9" W x .95" H Keyboard: 5.5" L x 4.5" W4 Line x 20 Character Supertwist (STN) LCDFull travel, Light touch 29 key alphanumeric 32 oz (907 grams)Six AA batteries - 200 hours of usage* *Based on 250kspm average data accumulation -4°F to 158°F, -20°C to 70°C -22°F to 176°F, -30°C to 80°C 0% to 90% (Operating and Storage) Multiple five foot drops to concrete 8KV Human modelPeripherals& Accessories
Display: Key switches: Keypad: Weight (including battery): Battery life: Operating Temperature: Storage Temperature: Humidity: Drop Spec: ESD: Communications:	11.63" L x 5.25" W x 3.88" H   Display: 2.9" W x .95" H   Keyboard: 5.5" L x 4.5" W   4 Line x 20 Character Supertwist (STN) LCD   Full travel, Light touch   29 key alphanumeric   32 oz (907 grams)   Six AA batteries - 200 hours of usage*   *Based on 250kspm average data accumulation   -4°F to 158°F, -20°C to 70°C   -22°F to 176°F, -30°C to 80°C   0% to 90% (Operating and Storage)   Multiple five foot drops to concrete   8KV Human model   Peripherals& Accessories   Flat file download application   USB cable
Display: Key switches: Keypad: Weight (including battery): Battery life: Operating Temperature: Storage Temperature: Humidity: Drop Spec: ESD: Communications: Communication cables:	11.63" L x 5.25" W x 3.88" H   Display: 2.9" W x .95" H   Keyboard: 5.5" L x 4.5" W   4 Line x 20 Character Supertwist (STN) LCD   Full travel, Light touch   29 key alphanumeric   32 oz (907 grams)   Six AA batteries - 200 hours of usage*   *Based on 250kspm average data accumulation   -4°F to 158°F, -20°C to 70°C   -22°F to 176°F, -30°C to 80°C   0% to 90% (Operating and Storage)   Multiple five foot drops to concrete   8KV Human model   Peripherals& Accessories   Flat file download application